



SUNIK INTERNATIONAL PVT. LTD.

Value & Performance
You can trust





WE DELIVER BEST



COMPANY ABOUT US

SUNIK TIRES IS PAVING THE ROAD TO A BETTER TIRE. **SUNIK TIRES** ARE OVERBUILT TO GUARANTEE SOLID PERFORMANCE AND CONSISTENTLY ENSURE YOU GET THE MOST OUT OF YOUR INVESTMENT. THEY ARE STRATEGICALLY DESIGNED DOWN TO THE SMALLEST DETAIL TO MEET TODAY'S MOST RUGGED CHALLENGES, WHETHER THAT'S AT THE TOP OF THE SUMMIT OR A ROAD TRIP IN A SNOWSTORM. TO KEEP UP WITH YOUR CHANGING NEEDS, **SUNIK TIRES** ENGINEERS ARE CONSTANTLY WORKING TO MAKE IMPROVEMENTS, ENHANCING DURABILITY AND OVERALL PERFORMANCE. WITH A RELENTLESS COMMITMENT TO BE THE BEST, ALL **SUNIK TIRES** EXCEED REGULATIONS AND STANDARDS TO ENSURE YOU CAN MOVE FORWARD SAFELY.

SUNIK BELIEVES AND IS WELL KNOWN FOR INNOVATION, QUALITY PERFORMANCE AND EXCELLENT CUSTOMER SERVICE.

SUNIK TIRES IS PAVING THE ROAD TO A BETTER TIRE. **SUNIK TIRES** TIRES ARE OVERBUILT TO GUARANTEE SOLID



CONTENTS

01	02	03	04	07	10	15	16
COMPANY ABOUT US	ENTERPRISE HONOR	ENTERPRISE BRAND	OFF-THE-ROAD TIRE	INDUSTRIAL TIRE	AGRICULTURAL TIRE	SOLID TIRE	TRUCK TIRE

ENTERPRISE HONOR





ENTERPRISE BRAND

STRONG R&D STRENGTH
MODERN EQUIPMENT
SCIENTIFIC **M**ANAGEMENT
CREATING **F**IRST-CLASS PRODUCTS



LANDE





WE DELIVER BEST

OFF THE ROAD TYRE



OFF THE ROAD TYRE



SIZE	PR	PATTERN NUMBER	STANDA RD RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAX LOADING Kg
7.50-15TT	6PR	C-1	6	-	785	215	400	1850
7.50-15TT	12PR	C-1	6	-	785	215	750	2650
8.5/90-15TL	6PR	C-1	6	-	785	220	350	1800
9.00-20TT	12PR	C-1	7	-	1015	255	625	4000
11.00-20TT	16PR	C-1	8	-	1080	290	725	5450

SIZE	PR	PATTERN NUMBER	STANDA RD RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAX LOADING Kg
20.5-25TT	16PR	C-2	17.00/2.0	16	1490	520	350	8250
23.1-26TL	12PR	C-2	DW20	16	1500	595	200	5150
23.1-26TT	12PR	C-2	DW20	16	1500	595	200	5150
23.1-26TT	14PR	C-2	DW20	16	1500	595	230	5600



SIZE	PR	PATTERN NUMBER	STANDA RD RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAX LOADING Kg
12.5/70-16TL	6PR	L-2	10	16.5	848	316	200	1410
15.5/60-18TL	8PR	L-2	13	18	937	404	220	2195
13.00-24TL	16PR	L-2	9.00DC	23.5	1300	350	400	3200
13.00-24TL	12PR	L-2	9.00DC	23.5	1300	350	300	2725
14.00-24TL	16PR	L-2	9.00DC	25	1370	375	350	3650
14.00-24TL	12PR	L-2	9.00DC	25	1370	375	250	3070
15.5-25TL	12PR	L-2	12.00/1.3	23.5	1275	395	400	5600
17.5-25TL	12PR	L-2	14.00/1.5	26	1350	445	250	6150
17.5-25TL	16PR	L-2	14.00/1.5	26	1350	445	475	7300
20.5-25TL	16PR	L-2	17.00/2.0	29.5	1490	520	350	8250
23.5-25TT	16PR	L-2	19.00/2.5	31.5	1615	595	300	9500
23.5-25TL	16PR	L-2	19.00/2.5	31.5	1615	595	300	9500



L-3

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa 10km/h /50KM/h	MAXLOADING Kg 10km/h /50KM/h
8.25-16TT	14PR	L-3	6.50H	15	235	865	800	2300
16/70-20TT	14PR	L-3	13	23	1075	410	450/350	5150/2900
16/70-20TL	14PR	L-3	13	23	1075	410	450/350	5150/2900
16/70-24TT	14PR	L-3	13	23	1175	410	450/350	5600/3350
17.5-25TT	12PR	L-3	14.00/1.5	26	1350	445	350/225	6150/3650
17.5-25TT	16PR	L-3	14.00/1.5	26	1350	445	475/300	7300/4250
20.5-25TT	16PR	L-3	17.00/2.0	30	1490	520	350/275	8250/5450
23.5-25TT	16PR	L-3	19.00/2.5	33	1615	595	300/225	9500/6150
23.5-25TT	18PR	L-3	19.00/2.5	33	1615	595	335/255	10100/6700
23.5-25TT	20PR	L-3	19.00/2.5	33	1615	595	375/300	10900/7300
23.5-25TT	24PR	L-3	19.00/2.5	33	1615	595	475/350	12500/8000

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
17.5-25TL	16PR	L-4	14.00/1.5	46	1400	445	475	7300



L-4



EV4

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
23.5-25L	20PR	EV4	19.50/2.5	44	1615	595	375/300	10900/7300



L-5

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
17.5-25TL	16PR	L-5	14.00/1.5	63.5	1400	445	475	7300
20.5-25TL	20PR	L-5	17.00/2.0	71.5	1550	520	450	9500
23.5-25TL	20PR	L-5	19.50/2.5	78.5	1675	595	375	10900
26.5-25TL	28PR	L-5	22.00/3.0	87.5	1800	675	475	15500
29.5-25TL	28PR	L-5	25.00/3.5	95	1920	750	425	17500
29.5-25TL	32PR	L-5	25.00/3.5	95	1920	750	500	19500

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
20.5-25TL	20PR	KL-5	17.00/2.0	71.5	1550	520	450	9500
23.5-25TL	20PR	KL-5	19.50/2.5	78.5	1675	595	375	10900
23.5-25TL	24PR	KL-5	19.50/2.5	78.5	1675	595	475	12500



KL-5

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
15.5-25TL	12PR	E3	12.00/1.3	23.5	1275	395	400/250	5600/3250
15.5-25TL	16PR	E3	12.00/1.3	23.5	1275	395	475/325	6150/3750
17.5-25TL	12PR	E3	14.00/1.5	26	1350	445	350/225	6150/3650
17.5-25TL	16PR	E3	14.00/1.5	26	1350	445	475/300	7300/4250
20.5-25TL	16PR	E3	17.00/2.0	29	1490	520	350/275	8250/5450
20.5-25TL	20PR	E3	17.00/2.0	29	1490	520	450/325	9500/6000
23.5-25TL	16PR	E3	19.50/2.5	30	1615	595	300/225	9500/6150
23.5-25TL	20PR	E3	19.50/2.5	30	1615	595	375/300	10900/7300
26.5-25TL	24PR	E3	22.00/3.0	35	1750	675	400/300	14000/9250
26.5-25TL	28PR	E3	22.00/3.0	35	1750	675	475/350	15500/10000
29.5-25TL	28PR	E3	25.00/3.5	38	1875	750	425/325	17500/11500
29.5-25TL	32PR	E3	25.00/3.5	38	1875	750	500/400	19500/12800
29.5-29TL	28PR	E3	25.00/3.5	38	1975	750	425/325	19000/12150



E3



L-4S

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
18.00-25TL	32PR	L-4S	13.00/2.5	48	1675	500	750	15000



R-6

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
18.00-24TT	12PR	R-6	13.00/2.5	25	1615	500	275	8250



OFF THE ROAD RYRE

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
16/70-20 TT	14PR	R-5	13	25	1075	410	450	5150



R-5



T17

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
14.00-20TT	24PR	T17	10	25	1265	375	870	8500
14.00-24TT	24PR	T17	10	25	1370	375	850	9500
14.00-24TT	28PR	T17	10	25	1370	375	925	10000
14.00-24TT	28PR	T17	10	25	1370	375	925	10000



TI200

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10-16.5TL	8PR	TI200	8.25	30	773	264	410	1880
10-16.5TL	10PR	TI200	8.25	30	773	264	520	2135
12-16.5TL	12PR	TI200	9.75	30	831	307	550	2865
10.5/80-18TL	10PR	TI200	9	30	905	274	370	1950
12.5/80-18TL	12PR	TI200	9	30	985	308	370	2650
12.5/80-18TL	14PR	TI200	9	30	985	308	430	2910
16.9-24TL	14PR	TI200	DW15	24	1310	430	300	3530
19.5L-24TL	12PR	TI200	DW16	29.5	1315	495	230	3450
21L-24TL	14PR	TI200	DW18	32	1375	533	250	4200
16.9-28TL	14PR	TI200	DW15	24	1435	430	300	3765
16.9-30TL	14PR	TI200	DW15	24.5	1485	430	290	3705

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
18.00-25TL	40PR	E-4B	13.00/2.5	54	1675	500	950	17000



E-4B

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
14.00-24TL	16PR	TG-2	9.00DC	25	1348	362	350	3650



TG-2



E-4D

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
18.00-33TL	36PR	E-4D	13.00/2.5	71	1875	500	850	18500



G-6

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
13.00-25TT	28PR	G-6	10.00/1.5	24.5	1300	350	1050	9250





WE DELIVER BEST

INDUSTRIAL TYRE



Sunik International Pvt. Ltd.

INDUSTRIAL TYRE



EM500

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10-16.5TL	10PR	EM500	8.25	14	773	264	520	2135
10-16.5TL	8PR	EM500	8.25	14	773	264	410	1880
12-16.5TL	10PR	EM500	9.75	19	831	307	450	2540
23*8.5-12TL	6PR	EM500	7	13	574	213	340	820
27*8.5-15TL	6PR	EM500	7	15	678	213	350	1030

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10-16.5TL	10PR	RG400	8.25	18	773	264	520	2135
10-16.5TL	12PR	RG400	8.25	18	773	264	620	2375
10-16.5TL	8PR	RG400	8.25	18	773	264	410	1880
12-16.5TL	10PR	RG400	9.75	18	831	307	450	2540
12-16.5TL	12PR	RG400	9.75	18	831	307	550	2865



RG400



RG500

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10-16.5TL	10PR	RG500	8.25	19	773	264	520	2135
10-16.5TL	8PR	RG500	8.25	19	773	264	410	1880
12-16.5TL	10PR	RG500	9.75	19	831	307	450	2540
12-16.5TL	12PR	RG500	9.75	19	831	307	550	2865
14-17.5TL BIG DOG	14PR	RG500	10.5	22	921	349	550	3875
14-17.5TL NHS	14PR	RG500	10.5	24	921	349	550	3875
15-19.5TL BIG DOG	14PR	RG500	11.75	22	1019	389	480	4565
15-19.5TL NHS	14PR	RG500	11.75	24	1019	389	480	4565

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10-16.5TL	12PR	RG600	8.25	26	773	264	620	2375
12-16.5TL	14PR	RG600	9.75	32	831	307	620	3075



RG600

INDUSTRIAL TYRE



SK300

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10-16.5TL	10PR	SK300	8.25	15	773	264	520	2135
10-16.5TL	8PR	SK300	8.25	15	773	264	410	1880
12-16.5TL	10PR	SK300	9.75	18	831	307	450	2540
12-16.5TL	8PR	SK300	9.75	18	831	307	340	2180
27*10.5-15	8PR	SK300	9.75	15	691	259	410	1180



TI400

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10.00-20TT	16PR	TI400	7.5	20	1073	278	790	6085
8.25-20TT	14PR	TI400	6.5	20	992	236	830	4575
9.00-20TT	14PR	TI400	7	23	1038	259	760	5195

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
23*8.5-12TL	6PR	SK400	7	12	574	213	340	820
27*10.5-15TL	6PR	SK400	9.75	12.5	691	259	350	1090
27*10.5-15TL	8PR	SK400	9.75	12.5	691	259	410	1180
27*8.5-15TL	6PR	SK400	7	12	678	213	350	1030
27*8.5-15TL	8PR	SK400	7	12	678	213	410	1110
5.70-12TL	6PR	SK400	4.5	14	647	146	420	660



SK400



PLT328

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
15x41/2-8TT	8PR	PLT328	3.25x8	7.5	385	122	720	695
18*7-8TT	14PR	PLT328	4.33	12	465	168	900	1450
18*7-8TT	16PR	PLT328	4.33	12	465	168	1000	1650
21*8-9TT	14PR	PLT328	6	15	533	203	900	1950
21*8-9TT	16PR	PLT328	6	15	533	203	1000	2120
23*10-12TT	12PR	PLT328	8	14	597	254	700	2650
23*9-10TT	20PR	PLT328	7	13	584	229	1000	2650
250-15TT	16PR	PLT328	7.5	18.5	735	250	930	3855
250-15TT	20PR	PLT328	7.5	18.5	735	250	1080	4400
27*10-12TT	14PR	PLT328	8	18	682	254	700	2725
28*9-15TT	14PR	PLT328	7	17	706	221	970	3075
28*9-15TT	16PR	PLT328	7	17	706	221	1000	3250
300-15TT	20PR	PLT328	8	21	840	300	930	5940
4.50-12TT	8PR	PLT328	3	13	548	122	900	1175
5.00-8TT	10PR	PLT328	3.50	11	469	131	1000	1090
5.50-15TT	8PR	PLT328	4.50E	11	670	157	720	1670
6.00-15TT	10PR	PLT328	4.50	15	705	170	830	2185
6.00-9TT	10PR	PLT328	4.00	14	545	160	860	1515
6.00-9TT	12PR	PLT328	4	14	545	160	1030	1685
6.50-10TT	10PR	PLT328	5	13	597	178	790	1725
6.50-10TT	12PR	PLT328	5	13	597	178	970	1935
7.00-12TT	12PR	PLT328	5	15	683	192	860	2445
7.00-12TT	14PR	PLT328	5	15	683	192	1000	2670
7.00-15TT	12PR	PLT328	5.5	16	750	200	860	2870
7.00-15TT	14PR	PLT328	5.5	16	750	200	945	3100
7.50-15TT	12PR	PLT328	6.00	16	808	215	790	3140
7.50-15TT	14PR	PLT328	6	16	808	215	925	3375
8.25-15TT	12PR	PLT328	6.5	17	847	236	720	3545
8.25-15TT	14PR	PLT328	6.5	17	847	236	830	3830
8.25-15TT	16PR	PLT328	6.5	17	847	236	925	4045



SK600A

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
6.50-16TT	14PR	RG600A	5.50F	15	761	215	745	2400
7.00-16TT	16PR	RG600A	5.50F	17	800	215	810	2490
7.00-16TT	14PR	RG600A	5.50F	17	800	200	810	2020
7.50-16TT	14PR	RG600A	6.00F	12	834	215	745	2400
7.50-16TT	16PR	RG600A	6.00F	12	834	215	810	2490
7.00-16TT	14PR	RG600A	6.50F	14	867	235	630	1700
8.25-16TT	16PR	RG600A	6.50F	14	867	235	730	1800

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10-16.5TL	12PR	L4B	8.25	27	773	264	600	2375
12-16.5TL	14PR	L4B	9.75	33	831	307	560	3075



L4B



TI300

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10.00-20TT	16PR	TI300	7.5	20	1073	278	790	6085
9.00-20TT	14PR	TI300	7	20	1038	259	760	5195



INDUSTRIAL TYRE



PLT388

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
9.00-20TT	14PR	PLT338	7	22	1038	259	760	5195
10.00-20TT	16PR	PLT338	7.5	23	1073	278	790	6085
12.00-20TT	16PR	PLT338	8.5	25	1146	315	690	6980
12.00-20TT	18PR	PLT338	8.5	25	1146	315	900	8360
12.00-20TT	20PR	PLT338	8.5	25	1146	315	1000	8970

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
12.00-20TT	22PR	P222	8.5	22	1146	315	1050	9455
18*7-8TT	16PR	P222	4.33	12	465	168	1000	1650
21*8-9TT	14PR	P222	6	15	533	203	900	1950
21*8-9TT	16PR	P222	6	15	533	203	1000	2120
23*9-10TT	16PR	P222	7	13	584	229	800	2300
23*9-10TT	18PR	P222	7	13	584	229	900	2430
250-15TT	16PR	P222	7.5	17.5	735	250	9825	3350
28*9-15TT	14PR	P222	7	17	706	221	1000	3000
300-15TT	20PR	P222	8	20	840	300	900	5000
5.00-8TT	10PR	P222	3.5	10.5	469	131	1000	1090
6.00-9TT	12PR	P222	4	13.5	545	160	1000	1450
6.50-10TT	12PR	P222	5	14	597	178	900	1650
7.00-12TT	12PR	P222	5	15	683	192	850	2060
7.00-12TT	14PR	P222	5	15	683	192	900	2120
7.00-15TT	14PR	P222	5.5	15	750	200	945	2500
7.50-15TT	14PR	P222	6	15	808	215	925	2800
8.25-15TT	14PR	P222	6.5	17	847	236	800	3250



P222

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
28*9-15TT	14PR	SD3000	7	17	706	221	970	3050
28*9-15TT	16PR	SD3000	7	17	706	221	1000	3115
6.00-9TT	10PR	SD3000	4	12	545	160	860	1505
6.50-10TT	10PR	SD3000	5	14	597	178	790	1655
7.00-12TT	12PR	SD3000	5	14	683	192	860	2375
7.00-15TT	12PR	SD3000	5.5	14	750	200	860	2870
7.00-15TT	14PR	SD3000	5.5	14	750	200	1000	3150
7.00-9TT	10PR	SD3000	5	12	590	190	860	1995
7.00-9TT	8PR	SD3000	5	12	590	190	750	1850
8.25-12TT	12PR	SD3000	6.5	13	765	235	720	3060
8.25-15TT	14PR	SD3000	6.5	16	840	235	830	3775



SD3000

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
18*7-8TT	16PR	SD2000	4.33	15	465	168	1000	1650
21*8-9TT	14PR	SD2000	6	20	533	203	900	1950
23*10-12TT	12PR	SD2000	8	18	597	254	700	2920
23*9-10TT	16PR	SD2000	7	18	584	229	800	2300
23*9-10TT	18PR	SD2000	7	18	584	229	900	2430
250-15TT	16PR	SD2000	7.5	18.5	735	250	930	4285
250-15TT	20PR	SD2000	7.5	18.5	735	250	1000	4475
27*10-12TT	14PR	SD2000	8	17	690	250	700	2725
28*9-15TT	14PR	SD2000	7	17	706	221	970	3415
300-15TT	20PR	SD2000	8	21	840	300	930	6575
5.00-8TT	10PR	SD2000	3.5	11.5	469	131	1000	1090
6.00-9TT	10PR	SD2000	4	13.5	545	160	860	1685
6.50-10TT	10PR	SD2000	5	14	597	178	790	1915
7.00-12TT	12PR	SD2000	5	14	683	192	860	2720
7.00-12TT	14PR	SD2000	5	14	683	192	1000	2965
7.00-15TT	12PR	SD2000	5.5	16	750	200	860	2150
7.00-15TT	14PR	SD2000	5.5	16	750	200	945	2270
7.50-15TT	12PR	SD2000	6	18	808	215	790	3490
7.50-15TT	14PR	SD2000	6	18	808	215	925	3640
7.50-16TT	12PR	SD2000	6	17	834	215	790	3195
8.25-15TT	12PR	SD2000	6.5	17	847	236	700	3000
8.25-15TT	14PR	SD2000	6.5	17	847	236	800	3250



SD2000



L6

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
18*7-8TT	16PR	L6	4.33	11	465	173	1000	1695
28*9-15TT	14PR	L6	7	12	706	220	970	3050
5.00-8TT	10PR	L6	3.5	10	469	137	1000	1150
6.00-9TT	10PR	L6	4	10	540	160	860	1505
6.00-9TT	12PR	L6	4	10	545	160	1030	1675
6.50-10TT	10PR	L6	5	13	590	175	790	1655
7.00-12TT	12PR	L6	5	14	676	192	860	2375
7.00-12TT	14PR	L6	5	14	676	192	1000	2670
7.00-15TT	12PR	L6	5.5	13	750	200	860	2870
7.00-15TT	14PR	L6	5.5	13	750	200	1000	3150
7.00-9TT	10PR	L6	5	10	590	190	860	1995
7.00-9TT	8PR	L6	5	10	590	190	750	1850
7.50-15TT	12PR	L6	6	15	808	215	790	3060
7.50-15TT	14PR	L6	6	15	808	215	925	3375
8.25-12TT	12PR	L6	6.5	13	765	235	720	3060
8.25-15TT	12PR	L6	6.5	15	840	235	720	3490
8.25-15TT	14PR	L6	6.5	15	840	235	830	3775
9.00-16TT	14PR	L6	6.5	15	890	255	760	4495

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
7.00-9TT	10PR	M12	5	10	590	190	860	1995



M12





WE DELIVER BEST

AGRICULTURAL TYRE



Sunik International Pvt. Ltd.

AGRICULTURAL TYRE



R-1



R-1

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXI-LOADING Kg
6.00-12TT	6PR	R-1 14	4.50E	22	640	165	250	405
6.00-12TT	6PR	R-1 16	4.50E	22	640	165	250	405
6.00-16TT	6PR	R-1	4.50E	24	745	165	250	495
6.50-16TT	6PR	R-1	5.00F	25	765	180	250	565
7.50-16TT	6PR	R-1 -18	5.50F	23	810	205	210	650
7.50-16TT	6PR	R-1 -16	5.50F	22	810	205	210	650
7.50-20TT	6PR	R-1	5.50F	26	910	205	210	760
8.3-20TT	6PR	R-1	W7	26	895	210	240	695
8.3-20TT	6PR	R-1	W7	26	895	210	240	695
8.3-24TT	6PR	R1	W7	26	995	210	240	810
8.3-24TT	6PR	R-1	W7	26	995	210	240	810
9.5-16TT	6PR	R-1	W8	23	860	240	210	800
9.5-20TT	6PR	R-1	W8	33	950	240	210	810
9.5-24TT	6PR	R-1	W8	30	1050	240	210	940
9.5-24TT	8PR	R-1	W8	30	1050	240	280	1110
10.00-15TT	8PR	R-1	8LB	19	855	276	240	1425
10/75-15.3TL	10PR	R-1	9	22	760	264	390	1090
11.2-20TT	8PR	R-1	W10	33	1005	285	240	1085
11.2-24TT	8PR	R-1	W10	33	1105	285	240	1225
11.2-28TT	6PR	R-1	W10	34	1205	285	180	1115
11.2-28TT	8PR	R-1	W10	34	1205	285	240	1305
11.2-28TT	8PR	R-1	W10	34	1205	285	240	1305
11.2-28TT	8PR	R-1	W10	34	1205	285	240	1305
11.5/80-15.3TL	10PR	R-1	9	24	845	290	350	1360
11-32TT	6PR	R-1	W10	44	1360	305	140	1000
11-38TT	8PR	R-1	W10	46.5	1540	305	180	1630
12.4-24TT	6PR	R-1	W11	36	1160	315	170	1200
12.4-24TT	6PR	R-1	W11	36	1160	315	170	1200
12.4-24TT	8PR	R-1	W11	36	1160	315	230	1415
12.4-28TT	6PR	R-1	W11	36	1260	315	170	1275
12.4-28TT	8PR	R-1	W11	36	1260	315	230	1510
12.4-32TT	6PR	R-1	W11	36	1360	315	170	1355
12-38TT	8PR	R-1	DW11	35	1575	330	140	1570
12-38TT	10PR	R-1	DW11	35	1575	330	220	1800
13.6/12-38TT	10PR	R-1	W12	35	1565	345	230	2215
13.6-24TT	8PR	R-1	W12	37	1210	345	210	1545
13.6-24TT	8PR	R-1	W12	37	1210	345	210	1545

Cont...

AGRICULTURAL TYRE

13.6-28TT	8PR	R-1	W12	33	1310	345	210	1645
13.6-28TT	10PR	R-1	W12	33	1310	345	250	1910
13.6-38TT	10PR	R-1	W12	36	1565	345	250	2215
14.9-24TT	10PR	R-1	W13	39	1265	378	230	1990
14.9-24TT	6PR	R-1	W13	39	1265	378	140	1510
14.9-24TT	8PR	R-1	W13	39	1265	378	180	1760
14.9-24TT	8PR	R-1	W13	39	1265	378	180	1760
14.9-24TT	8PR	R-1	W13	39	1265	378	180	1760
14.9-24TL	4PR	R-1 (TERRA)	W13	39	1265	378	100	1210
14.9-26TT	8PR	R-1	W13	38	1315	378	180	1820
14.9-26TT	8PR	R-1	W13	38	1315	378	180	1820
14.9-26TT	10PR	R-1	W13	38	1315	378	230	2055
14.9-30TT	10PR	R-1	W13	38	1415	378	230	2190
14.9-30TT	8PR	R-1	W13	38	1415	378	180	1940
15.5/80-24TL	12PR	R-1	W13	35	1240	394	300	2900
15.5/80-24TL	16PR	R-1	W13	35	1240	394	400	3300
15.5-38TT	10PR	R-1	W14L	36	1570	395	230	2320
15-24TT	10PR	R-1	DW14	35	1330	410	280	2800
15-24TT	10PR	R-1	DW14	35	1330	410	280	2800
15-24TT	12PR	R-1	DW14	35	1330	410	330	3100
16.9-28TT	10PR	R-1	W15L	39	1435	430	200	2380
16.9-28TT	10PR	R-1	W15L	39	1435	430	200	2380
16.9-28TT	8PR	R-1	W15L	39	1435	430	170	2175
16.9-30TT	10PR	R-1	W15L	40	1485	430	200	2455
16.9-30TT	8PR	R-1	W15L	40	1485	430	170	2245
16.9-34TT	10PR	R-1	W15L	39	1585	430	200	2605
16.9-34TT	8PR	R-1	W15L	39	1585	430	170	2380
16.9-38TT	8PR	R-1	W15L	39	1685	430	170	2520
16.9-38TT	10PR	R-1	W15L	39	1685	430	200	2760
18.4-26TT	8PR	R-1	DW16	38	1450	467	140	2265
18.4-26TT	8PR	R-1	DW16	38	1450	467	140	2265
18.4-26TT	12PR	R-1	DW16	38	1450	467	230	2985
18.4-26TL	12PR	R-1	DW16	38	1450	467	230	2985
18.4-30TT	8PR	R-1	W16L	41	1550	467	140	2415
18.4-30TT	10PR	R-1	W16L	41	1550	467	180	2815
18.4-34TT	8PR	R-1	W16L	38	1655	467	140	2565
18.4-34TT	10PR	R-1	W16L	38	1655	467	180	2990
18.4-38TT	8PR	R-1	W16L	41	1755	467	140	2715
18.4-38TT	10PR	R-1	W16L	41	1755	467	180	3165
18.4-38TT	10PR	R-1	W16L	41	1755	467	180	3165
18.4-42TT	10PR	R-1	W16A	51	1857	467	180	3330
18.4-42TT	10PR	R-1	W16A	51	1857	467	180	3330
18.4-42TT	12PR	R-1	W16A	51	1857	467	210	3750
20.8-38TT	10PR	R-1	W18L	42	1835	528	160	3475
20.8-42TT	12PR	R-1	W18L	42	1935	528	190	3750
23.1-26TT	12PR	R-1	DW20	42	1605	587	170	3610
405/70-20TL	14PR	R-1	13	37	1075	410	350	3250
405/70-24TL	14PR	R-1	13	37	1075	410	400	3550
16/70-20TT	10PR	R-1	13	35	1075	410	250	2300
16/70-20TL	10PR	R-1	13	35	1075	410	250	2300



R-1



R-2

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
9.5-20TT	8PR	R2	W8	60	976	240	280	955
12.4-24TT	8PR	R2	W11	67	1192	315	230	1415
13.6-38TT	8PR	R2	W12	70	1600	345	210	1910
18.4-34TT	10PR	R2	W16L	78	1702	467	180	2990
19.5L-24TT	10PR	R2	DW16	81	1357	495	170	1925
19.5L-24TT	12PR	R2	DW16	81	1357	495	210	2415
23.1-26TT	10PR	R2	DW20	88	1662	587	140	3245
23.1-26TT	12PR	R2	DW20	88	1662	587	170	3610
28L-26TT	14PR	R2	DW25	96.5	1672	715	170	4245

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
16.9-24TL	12PR	R4	W15L	27	1309	429	260	3250
16.9-28TL	12PR	R4	W15L	26	1410	429	200	2380
17.5L-24TL	10PR	R4	W15L	26	1241	445	220	2800
19.5L-24TL	12PR	R4	DW17	28	1314	495	230	3450
21L-24TL	14PR	R4	DW18	32	1378	533	250	4200



R-4



R-7

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
14.9-28TT	8PR	R7	W13	38	1365	378	180	1880
14.9-28TT	8PR	R7	W13	38	1365	378	180	1880
14.9-28TT	10PR	R7	W13	38	1365	378	230	2120
14.9-28TT	12PR	R7	W13	38	1365	378	280	2300
14.9-30TT	8PR	R7	W13	38	1415	378	180	1940
14.9-30TT	10PR	R7	W13	38	1415	378	230	2190



R-1



SR-1

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
18.4/15-30TT	12PR	KR-1	W16L	41	1550	467	230	3180



KR-1

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
13.6/12-38	10PR	SR-1	W12	36	1565	345	250	2215



AGRICULTURAL TYRE



WR-1

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
8.3-24TT	6PR	WR-1	W7	26	995	210	240	810
9.5-24TT	4PR	WR-1	W8	30	1050	240	140	670
11.2-24TT	4PR	WR-1	W10	34	1103	284	130	750
11.2-24TT	6PR	WR-1	W10	34	1103	284	180	950
11.2-28TT	4PR	WR-1	W10	30	1205	284	130	800
11.2-28TT	6PR	WR-1	W10	30	1205	284	180	1000
11.2-38TL	4PR	WR-1	W10	28.5	1459	284	120	950
11.2-38TT	6PR	WR-1	W10	28.5	1459	284	180	1150
12-38TT	8PR	WR-1	DW11	35	1575	330	140	1570
12.4-24TT	8PR	WR-1	W11	34	1159	315	220	1285
12.4-28TT	4PR	WR-1	W11	34	1260	315	110	900
12.4-28TT	6PR	WR-1	W11	34	1260	315	170	1130
13.6-28TT	6PR	WR-1	W12	34	1311	345	150	1285
13.6-28TT	8PR	WR-1	W12	33	1311	345	190	1500
13.6-38TT	6PR	WR-1	W12	34	1565	345	150	1500
14.9-24TT	4PR	WR-1	W13	35	1265	378	100	1210
14.9-24TT	6PR	WR-1	W13	35	1265	378	140	1360
14.9-24TT	8PR	WR-1	W13	35	1265	378	180	1600
14.9-28TT	6PR	WR-1	W13	35	1367	378	140	1450
15.5-38TT	8PR	WR-1	W14L	36	1569	394	180	1850
15.5-38TT	10PR	WR-1	W14L	36	1570	394	230	2320
16.9-24TT	6PR	WR-1	W15L	39	1333	429	120	1550
16.9-30TT	8PR	WR-1	W15L	38	1485	429	170	2000
16.9-38TT	8PR	WR-1	W15L	36	1685	429	170	2520
18.4-30TT	8PR	WR-1	W16L	39	1552	467	140	2180
18.4-30TT	10PR	WR-1	W16L	39	1552	467	180	2815
18.4-34TT	8PR	WR-1	W16L	41	1654	467	140	2300
18.4-34TT	10PR	WR-1	W16L	38	1654	467	180	2990
18.4-38TT	8PR	WR-1	W16L	38	1755	467	140	2430
18.4-38TT	10PR	WR-1	W16L	38	1755	467	180	3165
20.8-38TT	8PR	WR-1	18	51	1834	528	120	2800

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
11.2-24TL	4PR	WR-1(IRRIIGATION TYRE)	10	28	1097	285	190	750
14.9-24TL	4PR	WR-1(IRRIIGATION TYRE)	13	30.5	1260	366	80	1000



WR-1 (IRRIIGATION TYRE)



KR-4

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
16.9-28TL	12PR	KR-4	W15L	26	1435	429	260	3450

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
5-12TL	6PR	G-1	3.00D	13	528	127	360	285
6-14TL	6PR	G-1	5	15	627	155	290	300
7-14TL	6PR	G-1	5	16	691	183	250	450
6-16TL	6PR	G-1	4.50E	25	745	165	290	426
7-16TL	6PR	G-1	6	27	744	183	250	500
8-16TL	6PR	G-1	6	17	790	211	195	617
9.5-16TL	6PR	G-1	8	18	845	241	210	630



G-1



PR-1

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
6.50-16TT	6PR	PR-1	5.00F	65	805	173	250	565
7.50-16TT	6PR	PR-1	5.50F	73	910	205	210	650
7.50-16TT	6PR	PR-1	5.50F	73	810	200	210	880
8.3-20TT	6PR	PR-1	W7	78	950	210	270	970
8.3-24TT	6PR	PR-1	W7	78	1050	210	270	1135
9.00-20TT	6PR	PR-1	W8	78	1034	228	210	750
9.5-20TT	6PR	PR-1	W8	70	1050	240	240	1140
9.5-24TT	6PR	PR-1	W8	78	1150	240	240	1315
9.5-24TT	8PR	PR-1	W8	78	1150	240	310	1420
11.2-24TT	6PR	PR-1	W10	85	1205	285	210	1465
11-32TT	6PR	PR-1	W10	94	1460	305	160	1080
12.4/11-28TT	6PR	PR-1	W11	84	1315	315	200	1785
12.4/11-28TT	8PR	PR-1	W11	84	1315	315	220	1900
12.4-24TT	8PR	PR-1	W11	85	1245	315	230	1980
13.6-38TT	10PR	PR-1	W12	90	1710	345	250	2780
14.9-30TT	10PR	PR-1	W13	100	1560	378	260	2410
14.9-30TT	8PR	PR-1	W13	100	1560	378	210	2200
16.9-30TT	8PR	PR-1	W15L	90	1585	430	170	2245
16.9-30TT	10PR	PR-1	W15L	90	1585	430	200	2455
16.9-34TT	10PR	PR-1	W15L	90	1687	430	220	3385



AGRICULTURAL TYRE

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
4.00-14TT	6PR	F-1	3.00D	17	590	110	380	350
4.00-16TT	6PR	F-1	3.00D	17	640	110	380	380
4.50-16TT	8PR	F-1	3.00D	18	655	120	400	610
5.00-15TT	8PR	F-1	41	19	665	140	530	565
5.00-16TT	6PR	F-1	41	15	710	150	370	525
6.00-16TT	6PR	F-1	4.00E	14	740	160	340	560
6.00-16TT	6PR	F-1 F-1	4.00E	14	740	160	340	560
6.50-20TT	6PR	F-1	5.00F	14	860	180	310	725
6.50-20TT	8PR	F-1	5.00F	14	860	180	420	865
6.50-20TT	6PR	F-1 F-1	5.00F	14	860	180	310	725
7.50-16TT	8PR	F-1	5.50F	19	810	205	370	870
7.50-16TT	6PR	F-1	5.50F	19	810	205	280	745
7.50-18TT	8PR	F-1	5.50F	20	860	205	370	945
7.50-20TT	8PR	F-1	5.50F	19	910	205	370	1020
7.50-20TT	6PR	F-1	5.50F	19	910	205	280	875
11.00-16TT	8PR	F-1	W10L	28	970	315	250	1320



F-1



F-2

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
5.50-16TT	6PR	F-2	4.00E	13	713	150	370	525
6.00-16TT	6PR	F-2	4.00E	14	739	159	340	560
6.50-16TT	6PR	F-2	4.50E	14	761	173	310	615
7.50-16TT	6PR	F-2	5.50F	18	808	203	280	745
10.00-15TT	8PR	F-2	8LB	9	855	276	240	1425
10.00-15TT	10PR	F-2	8LB	9	855	276	320	1660

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10.00-16TT	8PR	F-2(4RIB)	W8L	16	894	274	300	1060
10.00-16TL	10PR	F-2(4RIB)	W8L	16	894	274	390	1280
10.00-16TT	10PR	F-2(4RIB)	W8L	16	894	274	390	1280
11.00-16TT	8PR	F-2(4RIB)	W10L	16	967	315	280	1180
11.00-16TL	10PR	F-2(4RIB)	W10L	16	967	315	345	1350
11.00-16TL	12PR	F-2(4RIB)	W10L	16	967	315	410	1550
11L-15TT	8PR	F-2(4RIB)	8	21	815	274	300	950



F-2(4RIB)



F-2(BRIB)

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
4.00-15TL	4PR	F-2(3RIB)	3.00D	9	616	112	360	265
4.00-15TT	4PR	F-2(3RIB)	3.00D	11.5	620	114	360	265
4.00-19TL	4PR	F-2(3RIB)	3.00D	10	717	112	360	325
5.00-15TL	4PR	F-2(3RIB)	41	13	664	130	300	325
5.50-16TL	6PR	F-2(3RIB)	4	13	713	150	390	475
5.50-16TT	6PR	F-2(3RIB)	4	13	713	150	390	475
6.00-16TL	6PR	F-2(3RIB)	4	10	739	159	360	515
6.00-16TT	6PR	F-2(3RIB)	4	10	739	159	360	515
6.50-16TL	6PR	F-2(3RIB)	4.5	14	761	173	330	560
6.50-16TT	6PR	F-2(3RIB)	4.5	14	761	173	330	560
7.50-16TL	10PR	F-2(3RIB)	5.5	19	808	203	390	775
7.50-16TL	6PR	F-2(3RIB)	5.5	19	808	203	300	670
7.50-16TL	8PR	F-2(3RIB)	5.5	19	808	203	390	775
7.50-16TT	10PR	F-2(3RIB)	5.5	19	808	203	430	860
7.50-16TT	8PR	F-2(3RIB)	5.5	19	808	203	390	775
10.00-16TL	10PR	F-2(3RIB)	W8L	23	894	274	390	1280
10.00-16TT	10PR	F-2(3RIB)	W8L	23	894	274	390	1280
11.00-16TL	10PR	F-2(3RIB)	W10L	23	967	315	345	1350
11.00-16TT	10PR	F-2(3RIB)	W10L	23	967	315	345	1350
11.00-16TT	12PR	F-2(3RIB)	W10L	23	967	315	410	1550
7.5L-15TT	6PR	F-2(3RIB)	6	15.5	742	203	300	650
9.5L-15TT	8PR	F-2(3RIB)	7	24	777	239	330	850
11L-15TT	8PR	F-2(3RIB)	8	21	815	274	300	950



F-3

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
11L-15TL	10PR	F-3	8LB	11	813	279	360	1060
11L-16TL	12PR	F-3	8LB	11	838	279	440	1250
11L-16TL	10PR	F-3	8LB	11	838	279	360	1120
14.5/75-16.1TL	10PR	F-3	11LB	15	940	373	280	1450

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10/75-15.3TL	10PR	IMP100	9	9	760	264	400	1550
10/75-15.3TL	12PR	IMP100	9	9	760	264	470	1700
10/75-15.3TL	14PR	IMP100	9	9	760	264	550	1900
11.5/80-15.3TL	10PR	IMP100	9	10	845	290	340	1950
11.5/80-15.3TL	12PR	IMP100	9	10	845	290	410	2180
11.5/80-15.3TL	14PR	IMP100	9	10	845	290	470	2430
12.5/80-15.3TL	14PR	IMP100	9	10	889	307	440	2650



IMP100



AGRICULTURAL TYRE



IMP600

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
10.5/80-18TL	10PR	IMP600	9	22	907	274	370	1950
10.5/80-18TL	12PR	IMP600	9	22	907	274	430	2075
12.5/80-18TL	12PR	IMP600	9	25.5	987	308	370	2625
12.5/80-18TL	14PR	IMP600	9	25.5	987	308	430	2910



M-8

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
12.00-18TT	10PR	M-8	9.00V	18	1085	325	330	1800
12.00-18TT	12PR	M-8	9.00V	18	1085	325	420	2300

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
5.90-15TT	4PR	I-1	4.5	5.5	657.9	157.5	250	515
6.70-15TT	6PR	I-1	4.5	5	703.6	167.6	300	730
7.60-15TT	8PR	I-1	5.5	6.5	721.4	200.7	360	950
7.60-15TL	8PR	I-1	5.5	6.5	721.4	200.7	360	950
9.5L-14TT	8PR	I-1	8	6	741	241	300	1090
9.5L-14TL	8PR	I-1	8	6	741	241	300	1090
9.5L-15TL	8PR	I-1	8LB	6	767	241	300	1120
9.5L-15TT	8PR	I-1	8LB	6	767	241	300	1120
11L-14TT	6PR	I-1	8KB	6	752	279	190	925
11L-14TT	8PR	I-1	8KB	6	752	279	250	1100
11L-15TL	8PR	I-1	WBL	6	777	279	250	1150
11L-15TT	8PR	I-1	WBL	6	777	279	250	1150
11L-15TT	12PR	I-1	WBL	6	777	279	360	1450
11L-15TL	12PR	I-1	WBL	6	777	279	360	1450
12.5L-15TT	8PR	I-1	10	6	823	318	250	1360
12.5L-15TL	8PR	I-1	10	6	823	318	250	1360
12.5L-15TT	10PR	I-1	10	6	823	318	300	1550
12.5L-15TL	10PR	I-1	10	6	823	318	300	1550
12.5L-15TT	12PR	I-1	10	6	823	318	360	1750
12.5L-15TL	12PR	I-1	10	6	823	318	360	1750
11L-14TT	6PR	I-1	8	6.5	747	274	190	925
11L-14TT	8PR	I-1	8	6.5	747	274	250	1100
11L-16TT	8PR	I-1	8	6.4	798	274	250	1215
12.5L-16TL	12PR	I-1	10	10	841	312	360	1800



I-1



M-9

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
7.50-16TT	6PR	M-9	5.00F	8	785	205	210	650
11.2-20TT	10PR	M-9	W10	12	1005	285	300	1250
11.2-20TT	4PR	M-9	W10	12	1005	285	130	760
12.4-24TT	6PR	M-9	W10	12	1105	315	170	1200
13-20TT	4PR	M-9	W12	10	1090	380	120	1050
26*9.5-12TT	4PR	M-9	5.50F	9	660	205	180	370
31*9.5-16TT	4PR	M-9	6.00F	8	790	220	160	850





WE DELIVER BEST

SOLID TYRE



SOLID TYRE



3-00D

SIZE	PR	PATTERN NUMBER	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
4.00-8	SP800	3.00D	22	423	121	1090	840
5.00-8	SP800	3.00D	25	469	146	1255	965
6.00-9	SP800	4.00E	26	545	160	1975	1520
6.50-10	SP800	5.00F	30	597	178	2715	2090
7.00-12	SP800	5.00S	26	683	192	3105	2390
7.00-15	SP800	5.5	31	759	204	3700	2845
7.00-9	SP800	5.00S	30	578	186	2670	2055
7.50-15	SP800	6.5	35	774	215	4490	3455
8.25-12	SP800	5.00S	33	735	236	3425	2635
8.25-15	SP800	6.5	36	847	236	5085	3910
8.25-15	SP800	5.5	36	847	236	4305	3310
18*7-8	SP800	4.33R	21	457	170	2430	1870
21*8-9	SP800	6.00E	25	535	207	2890	2225
23*9-10	SP800	6.50F	26	595	225	3730	2870
250-15	SP800	7	34	735	250	5220	4015
250-15	SP800	7.5	34	735	250	5595	4305
28*9-15	SP800	7	32	706	225	4060	3125





WE DELIVER BEST

TRUCK TYRE



TRUCK TYRE



B1

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
4.00-8TT	8PR	B1	3.00D	8	425	110	380	260
4.00-12TT	8PR	B1	3.00D	8	535	110	420	420
5.00-14TT	10PR	B1	4J	9	615	140	500	605
6.00-13TT	8PR	B1	4.50B	9	655	170	420	650
6.00-14TT	8PR	B1	4 1/2J	9	680	170	420	690
6.00-15TT	8PR	B1	4.50E	9	705	170	420	730
6.00-16TT	10PR	B1	4.50E	9	730	170	530	850
6.50-14TT	8PR	B1	4 1/2J	10	705	180	420	775
6.50-15TT	8PR	B1	4.50E	10	730	180	420	825
6.50-16TT	10PR	B1	5.50F	10	750	185	530	975
6.50-16TT	12PR	B1	5.50F	10	750	185	630	1060
6.50-16TT	14PR	B1	5.50F	10	750	185	730	1150
6.50-16TT	8PR	B1	5.50F	10	750	185	420	850
7.00-15TT	10PR	B1	5.50F	11	750	200	530	1030
7.00-15TT	14PR	B1	5.50F	11	750	200	730	1250
7.00-16TT	10PR	B1	5.50F	11	775	200	530	1090
7.00-16TT	12PR	B1	5.50F	11	775	200	630	1215
7.00-16TT	14PR	B1	5.50F	11	775	200	730	1320
7.00-16TT	16PR	B1	5.50F	11	775	200	830	1430
7.00-20TT	10PR	B1	5.5	13	904	200	630	1450
7.00-20TT	14PR	B1	5.5	13	904	200	840	1750
7.50-16TT	12PR	B1	6.00G	12	805	215	630	1400
7.50-16TT	14PR	B1	6.00G	12	805	215	730	1500
7.50-16TT	16PR	B1	6.00G	12	805	215	830	1600
7.50-20TT	14PR	B1	6	15	935	215	810	1900
8.25-20TT	14PR	B1	6.5	14	974	236	810	2240

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
6.50-16TT	12PR	B2	5.50F	10	750	185	630	1060
6.50-16TT	14PR	B2	5.50F	10	750	185	730	1150
7.00-16TT	14PR	B2	5.50F	11	775	200	730	1320
7.00-16TT	16PR	B2	5.50F	11	775	200	830	1450
7.50-16TT	14PR	B2	6.00G	12	805	215	730	1500
7.50-16TT	16PR	B2	6.00G	12	805	215	830	1600
8.25-16TT	14PR	B2	6.50H	14	855	235	630	1700
8.25-16TT	16PR	B2	6.50H	14	855	235	730	1800
9.00-16TT	6PR	B2	6.50H	14	890	255	280	1215
9.00-20TT	14PR	B2	7	14.5	1018	259	770	2575
9.00-20TT	16PR	B2	7	14.5	1018	259	880	2900
10.00-20TT	16PR	B2	7.5	14.5	1055	278	810	3000
10.00-20TT	20PR	B2	7.5	14.5	1055	278	1000	3570
11.00-20TT	16PR	B2	8	14.5	1085	293	810	3350
11.00-20TT	18PR	B2	8	14.5	1085	293	910	3650
12.00-20TT	18PR	B2	8.5	16	1125	315	810	3750
12.00-20TT	20PR	B2	8.5	16	1125	315	880	4000



B2

TRUCK TYRE

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
7.00-16TT	10PR	T1	5.50F	12	775	200	530	1090
7.00-16TT	12PR	T1	5.50F	12	775	200	630	1215
7.50-16TT	12PR	T1	6.00G	12	805	215	630	1400



T1



M7

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
7.50-16TT	8PR	M7	6.00G	17	805	215	420	1120
7.50-16TT	10PR	M7	6.00G	17	805	215	530	1250

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
8.5-16TT	10PR	R-3	6.50H	17	845	235	320	1095
8.5-16TT	12PR	R-3	6.50H	17	845	235	350	1150
8.5-16TT	14PR	R-3	6.50H	17	845	235	530	1475



R-3



HW100

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
14.00-24TT	24PR	HW100	10	25.5	1370	375	630	4580

SIZE	PR	PATTERN NUMBER	STANDAR D RIM	TREAD DEPTH	OVERALL DIAMETER mm	SECTION WIDTH mm	RELEVANT PRESSURE Kpa	MAXLOADING Kg
1500*600	22PR	Y-1	600*635	32	1500	600	380	5750
635TT								
15.5-20TT	22PR	Y-1	12	18	1260	420	700	6500



Y-1



WE DELIVER BEST







WE DELIVER BEST

SUNIK INTERNATIONAL PVT. LTD

HEAD OFFICE:- DSM 338, DLF TOWER, SHIVAJI MARG, NEW DELHI (INDIA) PIN CODE- 110015

Website:- www.sunikmotors.com, www.suniktires.com, www.sunikexports.com

Email:- sales@sunikmotors.com, sunikexports@gmail.com

HONG KONG OFFICE

22/F, CHEONG SUN TOWER,
116-118 WINT LOK STREET,
SHEUNG WAN, HONG KONG
TEL. : (852) 25430297 FAX: (852) 2543366

CHINA OFFICE

ROOM 322, TIME HERO BLDG NO. 1
ZHONGSHAN WEST ROAD,
HUITOU STREET, HAISHU DISTRICT,
NINGBO, CHINA
TEL.: (86) 574-87165444

SOUTH AMERICA OFFICE

SUQUE Y PEDRO CARBO ESQUINA,
EDIFICIA JOSE MARIA SAENAZ,
4TO PISO, OFICINA#401,
GUYAQUIL - ECUADOR
TEL.: (593-4) 2327382